

## This document was generated on 08/20/2019 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Γ	Part Number:	0039012041		
	Status:	Active		
	Overview:	Mini-Fit Jr. Power Connectors		
	Description:		al Row, 4 Circuits, UL 94V-2, with Panel Mounting Ears,	
		PS-45750-001-001 (PDF) PS-5556-001-001 (PDF)	Application Specification AS-5557-001-001 (PDF) Packaging Specification PK-5559-001-001 (PDF) RoHS Certificate of Compliance (PDF)	Series image - Reference only
	Agency Certification	I		<u>EU ELV</u>
	CSA		LR19980	Not Relevant
	UL		E29179	EU RoHS China RoHS
	General			Compliant
	Product Family		Crimp Housings	REACH SVHC
	Series		<u>5559</u>	Not Contained Per -
	3D Viewer		Yes	ED/71/2019 (16 July
	Application		Power, Wire-to-Board, Wire-to-Wire	2019)
	Comments		Current = 13A max. per circuit when header is mated	Halogen-Free
			to a receptacle loaded with $45750$ series terminals	<u>Status</u>
			crimped to 16 AWG wire See Molex product specification PS-45750-001 for additional current	Low-Halogen
			derating information.	For more information, please visit <u>Contact US</u>
	Comments		Current = 13A max. per circuit when header is mated	China ROHS Green Image
	Comments		to a receptacle loaded with $45750$ series terminals	ELV Not Relevant
			crimped to 16 AWG wire See Molex product	RoHS Phthalates Not Contained
			specification PS-45750-001 for additional current	
			derating information.	
	Overview		Mini-Fit Jr. Power Connectors	Search Parts in this Series
	Product Name		Mini-Fit Jr.	5559 Series
	UPC		800753584303	
	Physical			Mates With
	Breakaway		No	Dual Row Receptacle Housing <u>5557</u>
	Circuits (maximum)		4	<pre></pre>
	Color - Resin		Natural	<pre></pre>
	Flammability		94V-2	
	Gender		Plug	Use With
	Glow-Wire Capable		No	<u>5558</u> , <u>30490</u> Male Terminal, <u>46012</u> Mini-Fit
	Material - Resin		Nylon	Plus Crimp Terminal
	Net Weight		1.744/g	,
	Number of Rows		2	
	Packaging Type		Bag	
	Panel Mount		Yes 4.20mm	
	Pitch - Mating Interface Pitch - Termination Interface		4.20mm	
	Polarized to Mating Pa		Yes	
	Stackable		No	
	Temperature Range -	Operating	-40° to +105°C	
	Electrical		40.04	
	Current - Maximum pe	er Contact	13.0A	
	Solder Process Data	I		
	Lead-freeProcess Ca	pability	N/A	

Material Info Engineering Number

**Reference - Drawing Numbers** Application Specification Packaging Specification Product Specification Sales Drawing 5559-04P

AS-5557-001-001 PK-5559-001-001 PS-45750-001-001, PS-5556-001-001 SD-5559-NP-000

This document was generated on 08/20/2019 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION