



OPERATING FEATURES		
FEATURE	UNIT	VALUE
V max	V	32
T. min - T. max	°C	-30 / +85
* I Global Continuous	A	135
IP	IEC 529	23

* APPLICATION WITH GLOBAL CURRENT HIGHER THAN THE INDICATED ONE, HAVE TO BE VERIFIED AND AUDITED ONE BY ONE

UNCONTROLLED COPY
in case of drawing updating/revision
NO AUTOMATIC
resubmission will follow

Pos.	Q.ty	DENOMINATION	MATERIAL
6	2	SECONDARY LOCK	PA 66 V2 - YELLOW COLOR
5	16	MALE TERMINAL	CuSn Tin Plated
4	1	GASKET	NBR 70 - BLACK COLOR
3	2	THREADED INSERT	CuZn
2	1	BODY	PA 66-GF30 HB - BLACK COLOR
1	1	COVER	PA 12 V2 - TRANSPARENT

MTA		MTA P/N	0100580		Denom. FUSE BOX UNIVAL AXIAL 8WAY	
Rel. Level		Draw No.	B0-002.009A		Used for	
APPROVED		Draw for	CLIENT		Relevant Standard	
Date	Name	Scale	Weight(g)	Lin.Tol.±	Ang.Tol.±	Material SEE TABLE
Draft.	29/01/1997	I.MASSARI	1:1	65.6	0.5	Thick.
Chk	29/01/1997	I.MASSARI				Width
PQApp	13/05/2009	R.GONZALEZ	A3	Dimensions in (mm)	Sheet 1/1	Coating SEE TABLE
App.	13/05/2009	M.CORBANI				Color SEE TABLE

4	P/N MTA MODIFIED, IT WAS 0300580	
No.	Reason for Revision	Date 11/05/2009 Name S.BEDUSCHI

All proprietary rights reserved by MTA S.p.A. - This drawing shall not be reproduced, or in any way utilized, for the manufacture of the component or unit herein illustrated and must not be released to other parties, without written consent. Any infringement will be legally pursued.